

Delock 2.5" External Enclosure SATA HDD > Multiport SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) (up to 15 mm HDD)

Description

In the aluminum enclosure by Delock a 2.5" SATA hard drive or SSD can be installed. The enclosure can be connected via USB Type-C™ to the PC or laptop. By using optional cable, it is possible to connect this enclosure to a USB Type-A, eSATA or eSATAp interface. The enclosure is especially suitable for different hard disk with a height up to 15 mm.



Item no. 42556

EAN: 4043619425563

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Specification

- Connector:
external:
1 x Multiport SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) + eSATAp 6 Gb/s
1 x DC for power when connecting via eSATA
internal:
1 x SATA 6 Gb/s 22 pin
- Suitable for 2.5" SATA HDD / SSD:
HDD height up to 15 mm
SATA HDD / SSD up to 6 Gb/s
HDD / SSD up to 4 TB
supports 5 V HDD / SSD
- Chipset: Asmedia ASM1351 + ASM1456
- Data transfer rate:
SuperSpeed USB 10 Gbps,
SuperSpeed USB 5 Gbps,
Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,
Low-Speed 1.5 Mbps
eSATA 6 Gbps

- Enclosure with full-PCB
- LED indicator for power
- Colour: black
- Dimensions (LxWxH): ca. 136 x 80 x 21 mm
- Hot Swap, Plug & Play

Specification of power connector

- 5 V, ground outside, plus inside
- Dimensions:
inside: ø ca. 1.35 mm
outside: ø ca. 3.5 mm
length: ca. 8.5 mm
- Optional power supply: [Navilock 41337](#)

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port

Package content

- 2.5" external enclosure
- Cable USB Typ-A male to USB-C™ male, length ca. 50 cm
- Cover, screwdriver, screws
- User manual

Images



General

Function:	Hot Swap Plug & Play
Suitable for data medium:	2.5" SSD or HDD height up to 15.0 mm up to 4 TB
Internal construction:	full PCB
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x Multiport USB 10 Gbps + eSATAp 6 Gb/s 1 x 5 V DC jack 3.5 mm x 1.35 mm
Internal:	1 x SATA 6 Gb/s 22 pin

Technical characteristics

Chipset:	Asmedia ASM1456 Asmedia ASM1351
Data transfer rate:	10 Gbps

Physical characteristics

Housing material:	Aluminium
Length:	136 mm
Width:	80 mm
Height:	21 mm
Colour:	black