



#### NOTES:

##### ELECTRICAL:

1. VOLTAGE RATING : 125V AC RMS
2. CURRENT RATING : 1.5A mp
3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
6. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 B.2-1 ISO/IEC 11801:2002 CLASS EA

##### ENVIRONMENTAL:

1. STORAGE : -40° TO+85°
2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5  
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68  
MECHANICAL

1. RJ45 JACK LIFE: 750 TIMES MIN
2. IDN LIFE : 200 TIMES MTN

⑦	Upper Panel Cover	1.2mm thickness Metallic Panel with plastic powder cladding	1	
⑥	Bottom Panel :	1.5mm thickness Metallic Panel with plastic powder cladding	1	
⑤	RJ45 Jack :	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	8	
④	PCB	1.6mm UL 94V0	1	
③	IDC BODY	Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B	8	
②	IDC PIN	Phosphor Bronze & Tinned	64	
①	IDC TERMINAL	For 22-24 AWG Cable	8	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

<b>DELCK®</b> we move the world			
Title: Desktop Patch Panel 8 Port Cat.6A grey			
Dat	2016 / 01 / 06	Item no.	87289
Unit	mm	Barcode	4043619872893
Projection		File No.	88220
Rev	A		