

NOTES:

ELECTRICAL:

- | | |
|---------------------------|-------------------------------------|
| 1. VOLTAGE RATING | : 125V AC RMS |
| 2. CURRENT RATING | : 1.5A mmp |
| 3. CONTACT RESISTANCE | : 100 MILLI OHMS MAX |
| 4. INSULATION RESISTANCE | : 1000M OHMS MIN @ 500V DC |
| 5. DIELECTRIC STRENGTH | : 750V AC RMS 60Hz, 1MIN |
| 6. CAT. 6A PERMANENT LINK | : CONFORM TO ANSI/TIA/EIA-568 B.2-1 |
| ENVIRONMENTAL: | ISO/IEC 11801:2002 CLASS EA |

ENVIRONMENTAL:



- | | |
|--------------|----------------|
| 1. STORAGE | : -40° TO +85° |
| 2. OPERATION | : 0° TO +70° |

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

1. RJ45 JACK LIFE: 750 TIMES MIN
2. IDN LIFE : 200 TIMES MIN

⑦	Upper Panel Cover	1.2mm thickness Metallic Panel with plastic powder cladding	1	
⑥	Bottom Panel :	1.5mm thickness Metallic Panel with plastic powder cladding	1	
⑤	R/45 Jack :	Housing-Fireproof PBr UL-94V0 Pin-8P8C 3u" gold plated	8	
④	PCB	1.6mm UL 94V0	1	
③	IDC BODY	Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B	8	
②	IDC PIN	Phosphor Bronze & Tinned	64	
①	IDC TERMINAL	For 22-24 AWG Cable	8	
NO.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARK

	
Title: Desktop Patch Panel 8 Port Cat.6A black	
Unit	mm
Projection	
Rev	A
Item no.	87674
Barcode	4043619876747
File No.	88220