



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 12V AC RMS
- 2. CURRENT RATING : 1.5amp
- 3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 50Hz, 1MIN
- 6. CAT. 6 PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 B.2-1 ISO/IEC 11801:2002 CLASS E

ENVIRONMENTAL:

- 1. STORAGE : -40° TO+80°
- 2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5 MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

MECHANICAL

- 1. SHIELD MATERIAL BRASS C2680 T=0.25MM
- 2. HOUSING MATERIAL PBT+15%GF UL94V0
- 3. CONTACT MATERIAL PHOSPHOR BRONZE PLATING GOLD
- 4. PANEL FRAME ZN PLATING
- 5. IDC MATERIAL: PC UL94V0 TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 6. RJ45 JACK LIFE: 750 TIMES MIN
- 7. IDC LIFE : 200 TIMES MIN
- 8. RETENTIVENESS OF INSERTION STRUCTURE: 50N 50±5s

Accessory:

- 1. Cable Tie(75X1.9mm) X24Pcs
- 2. Instruction Sheet
- 3. Screw and Nut M6*18mm x 2set
- 4. Cabel Stripper X 1 Pcs
- 5. Silica gel 3.5G x 1PCS

RoHS 2.0 & REACH COMPLIANT

MATERIAL LIST:

⑦	Bottom Panel	1.2mm thickness Metall Panel with plastic powder cladding	1	
⑧	Upper Panel Cover	1.0mm thickness Metall Panel with plastic powder cladding	1	
⑨	RJ45 Jack	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	24	
⑩	PCB	1.5mm UL-94V0 /With Coded Printing TT88A/B	3	
⑪	IDC Body	Fireproof PC/ABS UL-94V0	24	
⑫	IDC Pin	Phosphor Bronze & Tinned	192	
⑬	IDC Terminal	For 22-26 AWG Cable	24	
NO.	PARTS NAME	SPECIFICATION STANDARD		QT'Y
		REMARK		



Date	2017 / 01 / 10	Title:	19" Patch Panel 24 Port Cat.6 0.5 U
Unit	mm	Item no.	43315+43316
Projection		Barcode	4043619433155+4043619433162
Rev	A	File No.	