



SPECIFICATIONS

1.ELECTRICAL:

UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.
DIELECTRIC WITHSTANDING VOLTAGE : 1000 VOLTS AC.
WITHSTAND VOLTAGE TIME: 60S.
INSULATION RESISTANCE: 100 MΩ.
TERMINATION: RESISTANCE 20mΩ MAX AFTER ENVIRONMENTAL TESTING.

2.MECHANICAL:

CABLE-TO-PLUG TENSILE STRENGTH : 20POUND MIN.
DURABILITY : 200 MATING CYCLES.

3.MATERIAL & FINISH:

HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
COLOR : TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
CONTACT BLADE: COPPER ALLOY.
CONDUCTOR : STRANDED & SOLID WIRE , 24AWG, 26 AWG.
(It can be used for the wire OD from Ø 0.96~Ø1.02)
GOLD PLATING: 3u"~50u", ARE AVAILABLE.
SHIELDED SHELL: COPPER ALLOY.

| BLADE: | E | EB | Y | YB | Z | A | AE | AB | EC | AL | ZL | YBL |
|--------------|------|-----|-----|------|------|------|------------|-------|------|----|----|-----|
| Drawing | | | | | | | | | | | | |
| Mark | | | | | ✓ | | | | | | | |
| GOLD PLATING | 3Mu" | 3u" | 6u" | 15u" | 30u" | 50u" | CABLE TYPE | ROUND | FLAT | | | |
| Mark | | | | | | ✓ | Mark | | ✓ | | | |

DELICK®
we move the world

Title: RJ45 Crimp+Cut Plug Cat.5e STP

| | | | |
|------------|----------------|----------|---------------|
| Date | 2018 / 02 / 22 | Item no. | 86452 |
| Unit | mm | Barcode | 4043619864522 |
| Projection | | | |
| Rev | A | | |