


WIRING DIAGRAM					
Mini SAS 4i(HOST)			SATA internal cable rec.(TARGET)		
PLUG	PIN	SIGNAL	REC.	PIN	SIGNAL
P0	A2	RX0+	P1	6	TX+
	A3	RX0−		5	TX−
	B3	TX0−		3	RX−
	B2	TX0+		2	RX+
	GND GROUP			1,4,7	GROUND
	A5	RX1+	P2	6	TX+
	A6	RX1−		5	TX−
	B6	TX1−		3	RX−
	B5	TX1+		2	RX+
	GND GROUP			1,4,7	GROUND
	A13	RX2+	P3	6	TX+
	A14	RX2−		5	TX−
	B14	TX2−		3	RX−
	B13	TX2+		2	RX+
	GND GROUP			1,4,7	GROUND
	A16	RX3+	P4	6	TX+
	A17	RX3−		5	TX−
	B17	TX3−		3	RX−
	B16	TX3+		2	RX+
	GND GROUP			1,4,7	GROUND

GND GROUP:
A1,A4,A7,A12,A15,A18
B1,B4,B7,B12,B15,B18

Mini SAS 4i			8PIN HOUSING		
PLUG	PIN	SIGNAL	REC.	PIN	SIGNAL
P0	A8	SIDEBAND 7	P5	7	
	A9	SIDEBAND 3		5	
	A10	SIDEBAND 4		3	
	A11	SIDEBAND 5		1	
	B8	SIDEBAND 0		8	
	B9	SIDEBAND 1		6	
	B10	SIDEBAND 2		4	
	B11	SIDEBAND 6		2	

DELOCK®
we move the world

Title: Cable Mini SAS SFF-8087 >
4 x SATA 7 pin + Sideband 1 m metal

Date	2018 / 06 / 12	Item no.	85682
Unit	mm	Barcode	4043619856824
Projection			
Rev	A		