

TYPE:

1. CAT6 SHIELDED TOOLLESS CONNECTOR
2. COLOUR: SILVER

CABLE MATCHED:

1. SOILD AND STRANDED
2. 22AWG/23AWG/24AWG

ELECTRICAL:

1. CONTACT RESISTANCE: 20m OHM
2. INSULATION RESISTANCE: <=250M OHM @100 V DC
3. WITHSTAND VOLTAGE: DC1000V AC700V RMS 60HZ, 1MIN
4. CAT6 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA 568B. 2-10

ENVIRONMENTAL:

1. STORAGE: -40°/ +70°
2. OPERATION: -10°/ +60°


MECHANICAL:

1. MATERIAL: ZINC ALLOY
2. GOLD PINS: PHOSPHOR BRONZE, GOLD PLATING 3U"
3. TERMINAL PINS: PHOSPHOR BRONZE, ZIN PLATING
4. RJ45 CONTACT LIFE: 750 TIMES MIN
5. IDC TERMINAL LIFE: 250 TIMES MIN

DELOCK®

we move the world

Title: Coupler for network cable Cat.6
STP toolfree for installation

Date	2018 / 09/ 06		
Unit	mm	Item no.	86466
Projection		Barcode	4043619864669
Rev	A		