



SPECIFICATIONS

1.ELECTRICAL:

UL APPLICATIONS: 250 VOLTS AC MAX. AT 2 AMPS.
DIELECTRIC WITHSTANDING VOLTAGE : 1000 VOLTS AC. 60 SEC.
INSULATION RESISTANCE: 500 M .
CONTACT RESISTANCE: 20m MAX.
OPERATING AMBIENT TEMPERATURE: -20°C ~ 75°C.

2.MECHANICAL:

STRAIN RELIEF: 20POUND MIN.
DURABILITY: 1200 MATING CYCLES.

3.MATERIAL:

HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
CONTACT BLADE: COPPER ALLOY.
GOLD PLATING: 3u"-50u", ARE AVAILABLE.

4. USAGE:

SUITABLE FOR STRANDED & SOLID WIRE 23AWG ~ 26 AWG.

BLADE:	E	EB	Y	YB	Z	A	AE	AB	EC
Drawing									
Mark					✓				
GOLD PLATING	3Mu"	3u"	6u"	15u"	30u"	50u"	CABLE TYPE	FLAT	
Mark						✓	Mark	✓	

DELOCK®
we move the world

Title: RJ45 plug Crimp+Cut+Curve
Cat.6 STP

Date	2018 / 05 / 02	Item no.	86474
Unit	mm	Barcode	4043619864744
Projection		File No.	
Rev	A		