



USB 3.0
TYPE A PLUG

USB 3.0
TYPE B PLUG

WIRING MAP

| P1 | | P2 |
|-------|------------|-------|
| 1 | RED | 1 |
| 2 | WHITE | 2 |
| 3 | GREEN | 3 |
| 4 | BLACK | 4 |
| 5 | BLUE | 5 |
| 6 | YELLOW | 6 |
| 7 | DRAIN WIRE | 7 |
| 8 | PURPLE | 8 |
| 9 | ORANGE | 9 |
| SHELL | BRAID | SHELL |

ELECTRONIC TEST:

1. ALL CABLE 100% TEST, WITHOUT ANY OPEN CIRCUIT/SHORT CIRCUIT/MISMATCH
2. RESISTANCE: 2 ohm Max.
3. I. RESISTANCE: 20M ohm Min.
4. HI-POT: 300V DC/10ms

| Item | L (mm) | T (mm) |
|-------|--------|--------|
| 86777 | 500 | ±20 |
| 86778 | 1000 | ±20 |
| 86779 | 2000 | ±20 |

| NO | DESCRIPTION | QTY |
|----|---|-----|
| 1 | USB3.0 SERIES "A" PLUG | 1PC |
| 2 | USB3.0 SERIES "B" PLUG | 1PC |
| 3 | [7/0.127TA*1P+D(7/0.10TA)+AL+MY]*2C+7/0.127TA*1P+7*0.20TA*2C+F+AD(7/0.127B)B(16/6/0.12AL.M)OD=5.5mm PVC BLACK | 1PC |
| 4 | Stainless steel tube protective jacket | 1PC |

DELOCK
we move the world

Title USB 3.0 Cable Type-A male to Type-A male with metal jacket silver

| | | | |
|------------|----------------|----------|-------------------|
| Date | 2020 / 06 / 24 | Item no. | 86777 86778 86779 |
| Unit | mm | File No. | 88381 |
| Projection | | | |
| Rev | A | | |