



WIRING MAP				
P1				P2
1	RED			1
2	WHITE			2
3	GREEN			3
4	BLACK			4
5	BLUE			5
6	YELLOW			6
7	DRAIN WIRE			7
8	PURPLE			8
9	ORANGE			9
SHELL	BRAID			SHELL

Item	L (mm)	T (mm)
86774	500	±20
86775	1000	±20
86776	2000	±20

ELECTRONIC TEST:
1.ALL CABLE 100% TEST,WITHOUT ANY
OPEN CIRCUIT/SHORT CIRCUIT/MISMATCH
2.RESISTANCE:2 ohm Max.
3.I.RESISTANCE:20M ohm Min.
4.HI-POT:300V DC/10ms

NO	DESCRIPTION	QTY
1	USB3.0 SERIES"A"PLUG	1PC
2	USB3.0 SERIES"A"PLUG	1PC
3	[7/0.127TA*1P+D(7/0.10TA)+AL+MY]*2C+7/0.127TA*1P+7*0.20TA*2C+F+AD(7/0.127B)B(16/6/0.12AL.M)OD=5.5mm PVC BLACK	1PC
4	Stainless steel tube protective jacket	1PC

Date	2020 / 06 / 24	DELOCK® we move the world Title USB 3.0 Cable Type-A male to Type-A male with metal jacket silver	
Unit	mm		
Projection		Item no.	86774 86775 86776
Rev	A	File No.	88381