

Note:

1:All products must be 100% through the short circuit test.

2:Conditions:

1) DC:300V,1SEC.


2) Insulation Resistance:5MOHM.

Pin 1	black	Pin 4
Pin 2	red	Pin 3
Pin 3	white	Pin 2
Pin 4	yellow	Pin 1

wire list

This drawing is a controlled document for Iansan, It is subject to change and the controlling engineering organization should be contacted for the latest revision.			
6			
5			
4			
3	HY 2.0 Tinned Copper, Terminal	Silvery White	8PCS
2	HY 2.0 white shell	WHITE	2PCS
1	UL 1007-24# black, red, white, yellow cord, L=500mm, HY 2.0 , Male	BL, R, W, Y	4PCS

Tolerance:  
 0<, <1.0 ±0.05  
 1.0<,<4.0 ±0.10  
 4.0<,<8.0 ±0.15  
 9.0<,<15.0 ±0.30  
 15.0<,<30.0 ±1.0



Scale:Free Unit:mm

Date	2021 / 11 / 02	Title: Universal IOT Grove Cable 4 x pin male to 4 x pin male 40 cm	
Unit	mm	Item no.	86954
Projection		Barcode	4043619869541
Rev	A	File No.	88251

**DELOCK**  
 we move the world