



# NOTES:

- 1.ELECTRICAL TEST:100%OPEN,SHORT&MIS WIRE TEST.
- 2.CONTACT RESISTANCE:0.5hm,
- 3.INSULATOR RESISTANCE:5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

## PIN WIRING

VCC(5V)	P1
WHITE	B-
RED	A+
GREEN	GND

⑥	I.000001.0400R	TIE	TIE COLOR:BLACK L=100MM	1	PCS
⑤	C.045P01.0100R	MOLDING	PVC 45P BLACK	8.5	G
④	C.000000.0000R	MOLDING	PE	2.5	G
③	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	1.5	G
		IC	SP485EE IC	1	PCS
	J.0232RL.2800R	IC	FTDI FT232RL SOP28	1	PCS
	J.023011.0900R	PCB	USB RS485 PCB L=23.8 W=11.0	1	PCS
②	B.01004M.0N05R	CONNECTOR	USB A short body iron case nickel plated white rubber core sinking board type	1	PCS
①		CABLE	NO-UL 26AWG(16/0.10BC)*3C JACKET:BLACK 60P PVC OD:5.0±0.1MM	1	PCS
NO.	PART NO	ITEM	DESCRIPTION	Q'TY	UNIT

Delock 64242 : 0.5 m

Delock 63508 : 1 m

Delock 63509 : 2 m

Date	2023 / 04 / 06	Title: Adapter cable USB 2.0 Type-A to Serial RS-485 with 3 open wires	
Unit	mm	Item no.	64242 / 63508 / 63509
Projection		Barcode	
Rev	A	File No.	88203

**DELCK**  
we move the world