

Delock DisplayPort 1.2 KVM Switch 4K 60 Hz with USB 3.0 and Audio

Description

This KVM switch by Delock is a convenient solution for connecting two computers with DisplayPort output to a DisplayPort monitor. By using the button or a hotkey you can switch between both computers. Furthermore, two USB 2.0 ports for a mouse and keyboard, and two USB 3.0 ports for a hard drive or USB memory can be connected. With the support of MST (Multi-Stream Transport), multiple monitors can be used at the DisplayPort output with an optional MST hub.



Item no. 11467

EAN: 4043619114672 Country of origin: Taiwan,

Republic of China Package: Retail Box

Note

MST (Multi-Stream Transport) requires either monitors that are capable of DisplayPort 1.2 daisy-chaining, or use of a powered DisplayPort MST Hub. The PC source must be DisplayPort 1.2 MST compliant.

Specification

· Connectors:

Input:

2 x DisplayPort 20 pin female

2 x USB 3.0 Type-B female

2 x 3.5 mm 3 pin stereo jack female (audio)

1 x DC 5 V power connector

Output:

1 x DisplayPort 20 pin female

2 x USB 3.0 Type-A female (USB 3.0 Hub)

2 x USB 2.0 Type-A female (keyboard + mouse)

1 x 3.5 mm 3 pin stereo jack female (audio)

1 x 3.5 mm 4 pin stereo jack female (selector)

- Switch button with 2-colour LED indicator for source
- Switching via button or hotkey
- · Automatic switching when turning a PC on or off
- Independent switching of source, audio and USB 3.0 hub
- 2 x USB 3.0 Type-A female Battery Charging specification BC1.2

DATASHEET



- DisplayPort 1.2 specification
- Resolution up to 4096 x 2160 @ 60 Hz / 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- DisplayPort output supports Dual Mode DP++
- Supports MST (Multi-Stream Transport)
- · Robust metal housing
- Colour: black
- Dimensions (LxWxH): ca. 170 x 74 x 30 mm

Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 5 V / 4 A
- · Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm

System requirements

- PC with DisplayPort female + USB Type-A female
- Monitor or TV with DisplayPort connector

Package content

- . KVM switch with USB and audio
- 2 x cable USB 3.0 A male to USB 3.0 B male, length ca. 1.5 m
- 2 x cable DisplayPort male to DisplayPort male, length ca. 1.5 m
- 2 x cable 3.5 mm stereo jack male to 3.5 mm stereo jack male, length ca. 1.5 m
- 1 x selector with cable, length ca. 1.8 m
- External power supply
- User manual



Images









Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x DisplayPort female 2 x USB 5 Gbps Type-A female 2 x USB 2.0 Type-A female
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 2 x DisplayPort female 2 x USB 5 Gbps Type-B female 2 x 3.5 mm 3 pin stereo jack female

Technical characteristics

Maximum screen resolution:	4096 x 2160 @ 60 Hz
	3840 x 2160 @ 60 Hz

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	74 mm
Width:	170 mm
Height:	30 mm