

Delock Wall Socket with 2 x USB Type-A Charging Port 2.4 A

Description

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB Type-A charging ports. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.



Item no. 11471

EAN: 4043619114719 Country of origin: China

Package: Box

Specification

- Connectors:
 - 1 x power socket CEE 7/3 with childproof lock
 - 2 x USB Type-A charging port max. 2.4 A
 - 3 x screw terminal for PE, N, L
- · Robust plastic housing
- Rated current: 16 A / 250 V~
- Rated power: 4000 W
- USB Charger:

Input: AC 250 V / 50 Hz / 0.2 A

USB output: max. 5 V / 2.4 A total

Short circuit protection

- Suitable for standard installation box
- Dimensions (LxWxH): ca. 80 x 80 x 53 mm
- · Colour: white

System requirements





- Mains supply with grounding
- A free standard installation box

Package content

- Power socket
- User manual

Images











General

Mounting type:	in-wall
Protection:	Input overvoltage protection Short circuit protection

Interface

Connector 1:	1 x 3 pin terminal block screw terminal
Connector 2:	1 x Steckdose CEE 7/3 mit Kindersicherung
connector 3:	2 x USB Type-A female

Physical characteristics

Length:	80 mm
Width:	80.0 mm
Height:	56 mm
Colour:	white