

Delock Antenna Cable N plug > RP-SMA plug CFD400 LLC400 40 cm low loss

Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a very low attenuation.



Item no. 13018

EAN: 4043619130184

Country of origin: Taiwan,
Republic of China

Package: Box

Specification

- Connectors:
1 x N plug >
1 x RP-SMA plug
- Impedance: 50 Ohm
- Cable type: CFD400, LLC400
- Cable: coaxial
- Cable attenuation:
0.22 dB @ 2.4 GHz per meter
0.35 dB @ 5.7 GHz per meter
- Cable diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Cable colour: black
- Length incl. connectors (L): ca. 40 cm


System requirements

- Device with one free N or RP-SMA port

Package content

- Antenna cable

Images



Interface

| | |
|--------------|-------------|
| Connector 1: | N plug |
| Connector 2: | RP-SMA plug |

Technical characteristics

| | |
|------------|-------------|
| Impedance: | 50 Ω |
|------------|-------------|

Physical characteristics

| | |
|--------------------------|--|
| Cable type: | CFD400, LLC400 |
| Cable attenuation: | 2.4 GHz: ca. 0.22 dB per meter 5.7 GHz: ca. 0.35 dB per meter |
| Cable colour: | black |
| Cable length: | 0.4 m |
| Smallest bending radius: | 51.5 mm |