

# Delock External USB Type-C™ Combo Enclosure for M.2 NVMe PCIe or SATA SSD - tool free

## Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD or SATA M.2 SSD** in 2280, 2260, 2242 and 2230 format. It can be connected via USB to the PC or laptop. The **robust metal housing with cooling fins** ensures an optimum temperature of the memory.



## Combo enclosure

The big advantage of this Delock M.2 enclosure is that both SATA and PCIe (NVMe) M.2 SSDs can be inserted into the enclosure. The memory is **automatically recognized by the chipset** and can then be used.

**Item no. 42019**

EAN: 4043619420193

Country of origin: China

Package: Retail Box

## SSD installation without tools

The special feature of this enclosure is that **no tools** are required to install the M.2 SSD. The inner part can be pulled out by pushing the button, the SSD is inserted into the slot and attached to the board with a rubber nipple.

## Specification

- Connectors:  
external: 1 x USB 10 Gbps USB Type-C™ female  
internal: 1 x M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Bootable
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Metal housing

- Dimensions (LxWxH): ca. 110 x 38 x 13 mm
- Hot Plug, Plug & Play

## System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.2.3 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- PC or laptop with a free USB Type-C™ port
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- External enclosure M.2
- Cable USB-C™ male to USB-C™ male (with adapter to USB Type-A male), length ca. 45 cm
- 1 x thermal conductive pad
- 1 x thermal conductive plate
- 2 x rubber nipple
- User manual

## Images



## General

Function:	NVM Express (NVMe) Plug & Play
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Android 10.0 or above iPad Pro (3rd Generation) or above • iPad Air (2020) iPad Air (4th Generation) or above Mac OS 11.2.3 or above Windows 11 Linux Kernel 5.11 or above
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key M slot

## Technical characteristics

Chipset:	Realtek RTL9210B
Data transfer rate:	up to 10 Gbps

## Physical characteristics

Housing material:	Aluminium
Cable length:	45 cm
Length:	110 mm
Width:	38 mm



Height:	13 mm
Colour:	grey