

Delock 2.5" External Enclosure SATA HDD > Multiport USB 3.0 + eSATAp

Description

This aluminium-enclosure by Delock enables you to install a 2.5" SATA HDD or SSD and provides up to 4 different connecting options due to its special Multiport USB 3.0 + eSATAp interface. The Multiport is a combination of eSATA and USB 3.0 interface, which supports a fast data transfer and a voltage supply of up to 5 V. For extra voltage supply, when connecting via eSATA, you will find an additional power cable included in delivery.



- 1. USB 3.0 (Power via USB)
- 2. USB 2.0 (Power via USB)
- eSATAp (Power Over eSATA combo-connection eSATA+USB - eSATA for data and USB for power)
- 4. eSATA (eSATA for data and power via included USB power cable)



Item no. 42488

EAN: 4043619424887

Country of origin: Taiwan,

Republic of China

Package: Retail Box

Specification

• Connector:

external:

1 x Multiport USB 3.0 + eSATAp 6 Gb/s female

1 x DC for power when connecting via eSATA

internal:

1 x SATA 6 Gb/s 22 pin male

Suitable for 2.5" SATA HDD / SSD:

HDD height up to 9.5 mm

SATA HDD / SSD up to 6 Gb/s

HDD / SSD up to 3 TB

• Data transfer rate:

USB 3.0 up to 5 Gb/s

USB 2.0 up to 480 Mb/s

eSATA up to 6 Gb/s

- Enclosure with full-PCB
- · LED indicator for power
- · Colour: black

DATASHEET



- Dimensions (LxWxH): ca. 136 x 80 x 16 mm
- Hot Swap, Plug & Play

Specification of power connector

- 5 V, ground outside, plus inside
- Dimensions:

inside: ø ca. 1.35 mm outside: ø ca. 3.5 mm length: ca. 8.5 mm

Optional power supply: Navilock 41337

System requirements

- Windows Server-2003/Vista/7/7-64/8/8-64/8.1/8.1-64/10/10-64, Mac OS 10.8.2
- · PC or laptop with
 - 1. a free USB 3.0 port
 - 2. or a free USB 2.0 port
 - 3. or a free eSATAp port
 - 4. or o free eSATA port and a free USB port for power

Package content

- 2.5" external enclosure
- USB 3.0 cable
- Power cable
- eSATAp cable
- Cover, screwdriver, screws
- User manual



Images





General

Function:	Hot Swap Plug & Play
Suitable for data medium:	3.5" SSD or HDD height up to 9.5 mm up to 3 TB
Internal construction:	full PCB
Supported operating system:	Mac OS 10.8.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2003 32-bit Windows Vista 32-bit Windows Vista 64-bit

Interface

External:	1 x 5 V DC jack 3.5 mm x 1.3 mm 1 x Multiport USB 5 Gbps + eSATAp 6 Gb/s female
Internal:	1 x SATA 6 Gb/s 22 pin plug

Technical characteristics

Chipset:	Asmedia ASM1053
Data transfer rate:	USB 10 Gbps up to 10 Gb/s USB 2.0 up to 480 Mb/s eSATA up to 6 Gb/s

Physical characteristics





Cable length:	USB data cable: 50 cm eSATAp cable: 50 cm USB power cable: 80 cm
Length:	13.6 cm
Width:	8.0 cm
Height:	1.6 cm
Colour:	black