

# Delock 3.5" Mobile Rack for 1 x 2.5" SATA HDD / SSD

## Description

This Delock Mobile Rack is designed for external or internal connection of a 2.5" SATA HDD. Insert the HDD directly into the frame and connect it either externally to a free USB port or with the help of an optional cable to a Power Over eSATA port, or internally to SATA. The dimension of the frame complies to a standard 3.5" HDD. Thus you can install the frame into a 3.5" slot as well as into a 5.25" mobile rack.



**Item no. 47225**

EAN: 4043619472253

Country of origin: China

Package: Retail Box

## Specification

- Connector:
  - outside:
    - 1 x SATA 22 pin female
    - 1 x Micro USB 3.0 type B female
  - inside:
    - 1 x 22 pin SATA 6 Gb/s female ([NSS connector](#))
- Suitable for 2.5" SATA HDD / SSD:
  - HDD height up to 12.5 mm
  - SATA HDD / SSD up to 6 Gb/s
  - support 5 V HDD / SSD
- Data transfer rate up to 6 Gb/s
- Possible applications:
  1. internally in a 3.5" bay
  2. inside a 5.25" mobile rack
  3. externally over USB 3.0
  4. externally over eSATAp (cable optional)
- Hot Swap
- With special SATA NSS connector inside to protect the SATA connector of the HDD from wear at each change
- Optional HDD fan (mounting holes on the bottom side of mobile rack)
- OS independent, no driver installation necessary

## System requirements

- For external using:

1. PC or notebook with a free USB port
  2. PC or notebook with a free Power Over eSATA port  
(optional eSATAp cable item 84397 / 84396 / 84432)
- For internal using:
    1. PC with a free 3.5" bay
    2. PC with a free SATA port
    3. SATA connecting cable

## Package content

- Mobile Rack
- Screws
- USB 3.0 cable
- User manual

## Images



USB 3.0 micro B Schnittstelle



Anwendungsbeispiel



Anwendungsbeispiel