



Delock SATA 6 Gb/s Flash Module 128 GB MLC -40°C $\sim +85^{\circ}C$

Description

The Delock SATA 6 Gb/s flash module is, due to its small size, high shock resistance and an extended temperature range of -40°C +85°C most suitable for robust application in mobile devices such as IPCs and measuring systems, as well as for the digital signage range. The module supports the SATA 6 Gb/s standard and is therefore convenient for applications that require fast read and write speed. The metal clip on the SATA connector enables the module to snap in to your SATA port.



Item no. 54736

EAN: 4043619547364 Country of origin: Taiwan,

Republic Of China

Package: Antistatic cover

Specification

Capacity: 128 GB

• Interface: 7 pin SATA 6 Gb/s

• Chip: Toshiba Flash type: MLC • Maximum channel: 4

Maximum performance: 350 MB/s read, 130 MB/s write

Maximum write cycles: 3000

Maximum power consumption: 1.8 W (5 V x 370 mA)

• Thermal sensor: yes • Write protect: yes • ATA security: yes • S.M.A.R.T.: yes

Dimensions (LxWxH): ca. 41.5 x 25.2 x 6.8 mm

• Vibration: 20 G @7 ~ 2000 Hz Shock: 1500 G @0.5 ms • MTBF: >3 millionen hours

Storage temperature: -55°C ~ +95°C

Operation temperature: industrial grade -40°C ~ +85°C

System requirements

• A free SATA 7 pin port

· Power supply with a free 4 pin power connector

DATASHEET



Package content • SATA flash module

- Power cable