



Delock M.2 SATA 6 Gb/s SSD Industrial 8 GB (S42) Toshiba MLC -40 °C ~ 85 °C

Description

This flash module by Delok, with a length of 42 mm (2242), is a memory in M.2 format for the SATA interface. It supports the SATA 6 Gb/s specification and convinces with its effective boot time and a lower power consumption than common hard disk drives. The module supports the Delock iSmart function, is stable to vibration and has an extended temperature range from -40°C ~ +85°C. Delock iSmart is a powerful and easy-to-use monitoring tool. It allows system integrators to track important disk information, such as temperature, storage space, bad blocks, lifespan and firmware, all under one platform. The intelligent recovery system provides testing and data recovery during voltage fluctuations.



8 GB

Item no. 54787

EAN: 4043619547876

Country of origin: Taiwan,

Republic of China

Package: Antistatic cover

Note

The **Delock iSmart software tool** is available free of charge under the software section.

Specification

· Capacity: 8 GB

Connector: 59 pin M.2 key B+M male

 Interface: SATA 6 Gb/s • Form factor: M.2 2242

· Chip: Toshiba Flash Type: MLC • Maximum channel: 2

Maximum speed: read 140 MB/s - write 25 MB/s

Maximum write cycles: 3000

Maximum power consumption: 1.4 W (3.3 V x 422 mA)

· Thermal Sensor: yes

H/W Write protect: optional

· ATA security: yes

· iSmart.: yes

Dimensions (LxWxH): 42 x 22 x 3.2 mm

Vibration: 20G @ 7 ~ 2000 Hz

Shock: 1500G @ 0.5 Ms

• MTBF: >3 million hours

• Storage temperature: -55 °C ~ 95 °C

Operation temperature: Industrial grade -40 °C ~ 85 °C



System requirements

• A free M.2 port with key B or key M

Package content

• M.2 module





Interface

M.2 NGFF based on SATA connector:

Technical characteristics

Chipset:	Toshiba
Storage temperature:	-55°C - 95°C
Read:	140 MB/s
Maximum power consumption:	1.4 W
Maximum write cycles:	3000
MTBF:	3 million hours
Interface:	SATA 6.0 Gb/s
Shock:	1500 G @ 0.5 ms
Write:	25 Mb/s
Write protect:	optional
Capacity:	8 GB
Thermal sensor:	yes
Vibration:	20 G @ 7 ~ 2000 Hz
Delock iSmart:	Yes

Physical characteristics

Length:	42 mm
Width:	22 mm
Height:	3.2