

Delock M.2 SATA 6 Gb/s SSD Industrial 64 GB (S42) Toshiba MLC

Description

This flash module by Delock, with a length of 42 mm (2242), is a memory in M.2 format for the SATA interface. It supports the SATA 6 Gb/s specification and convinces with its effective boot time and a lower power consumption than common hard disk drives. The module supports the Delock iSmart function and is stable to vibration. **Delock iSmart** is a powerful and easy-to-use monitoring tool. It allows system integrators to track important disk information, such as temperature, storage space, bad blocks, lifespan and firmware, all under one platform. The intelligent recovery system provides testing and data recovery during voltage fluctuations.



The **Delock iSmart software tool** is available free of charge under the software section.



64 GB

Item no. 54791

EAN: 4043619547913

Country of origin: Taiwan,

Republic of China

Package: Antistatic cover

Specification

· Capacity: 64 GB

Connector: 59 pin M.2 key B+M male

Interface: SATA 6 Gb/sForm factor: M.2 2242

Chip: ToshibaFlash Type: MLCMaximum channel: 2

Maximum speed: read 530 MB/s - write 100 MB/s

Maximum write cycles: 3000

Maximum power consumption: 1.4 W (3.3 V x 422 mA)

· Thermal Sensor: yes

· H/W Write protect: optional

ATA security: yesiSmart.: yes

• Dimensions (LxWxH): 42 x 22 x 3.2 mm

• Vibration: 20G @ 7 ~ 2000 Hz

Shock: 1500G @ 0.5 MsMTBF: >3 million hours

• Storage temperature: -55 °C ~ 95 °C

Operation temperature: standard grade 0 °C ~ 70 °C





System requirements

• A free M.2 port with key B or key M

Package content

• M.2 module





Interface

M.2 NGFF based on SATA connector:

Technical characteristics

Chipset:	Toshiba
Storage temperature:	-55°C - 95°C
Read:	530 MB/s
Maximum power consumption:	1.4 W
Maximum write cycles:	3000
MTBF:	3 million hours
Interface:	SATA 6.0 Gb/s
Shock:	1500 G @ 0.5 ms
Write:	100 MB/s
Write protect:	optional
Capacity:	64 GB
Thermal sensor:	yes
Vibration:	20 G @ 7 ~ 2000 Hz
Delock iSmart:	Yes

Physical characteristics

Length:	42 mm
Width:	22 mm
Height:	3.2