



Delock USB Adapter 40 Gbps USB Type-C™ PD 3.0 100 W male to female rotated angled left / right 8K 60 Hz metal

Description

This USB-CTM adapter by Delock can be used for the connection of USB-CTM devices. It can be also connected to a free USB-CTM port in order to prevent the interface from damage when it is under usage for high contact durability.



Item no. 60048

EAN: 4043619600489 Country of origin: China Package: Zip poly bag

Specification

- · Connectors:
 - 1 x USB 40 Gbps USB Type-C™ male
 - 1 x USB 40 Gbps USB Type-C™ female
- Data transfer rate up to 40 Gbps
- USB Power Delivery (USB PD 3.0) support up to 100 watt
- Output current: up to 5 A
- Voltage: max. 20 V
- Supports DP Alt Mode
- Maximum resolution (depending on the system and the connected hardware):

DisplayPort 1.4 with DSC: up to 7680 x 4320 @ 60Hz

DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz

- Transmission of audio and video signals
- HDCP and HDR support
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Useable on both sides
- · Housing material: metal
- · Colour: anthracite



• Dimensions (LxWxH): ca. 2.5 x 1.2 x 0.9 cm

System requirements

• A free USB-CTM interface

Package content

• USB adapter

Images







General

Specification: USB Type-C™ USB4

Interface

Connector 1: 1 x USB Type-CTM male 1 x USB Type-C™ female Connector 2:

Technical characteristics

Operating voltage: 20 V Data transfer rate: 40 Gbps

Physical characteristics

Housing material:	metal
Length:	2.5 cm
Width:	1.2 cm
Height:	0.9 cm
Colour:	anthracite