



Delock Converter M.2 Key B+M male to 4 x SATA male with RAID and HyperDuo

Description

This converter by Delock expands the system by **four SATA ports**. When using more than one SATA port, there is the possibility to use different **RAID** modes. The converter supports a **hyperduo function**. With this function it combines an SSD and an HDD to use the advantages of both data mediums, the speed of an SSD and the capacity of an HDD.



Item no. 61062

EAN: 4043619610624 Country of origin: China

Package: Box

Specification

- Connectors:
 - 1 x M.2 key B+M male
 - 4 x SATA 6 Gb/s 7 pin plug
- · Chipset: Marvell
- Interface: PCIe 2.0
- Form factor: M.2 3042
- Suitable for M.2 slot with key M or B+M based on PCIe
- Data transfer rate up to 6 Gb/s
- Supports RAID 0, 1, 10, JBOD, HyperDuo Virtual Disk (Safe/Capacity)
- Supports HDD and SSD
- Supports Native Command Queuing (NCQ)
- Bootable
- Dimensions (LxWxH): ca. 42 x 30 x 13 mm

System requirements

• Linux Kernel 5.15 or above



- Windows 10/10-64/11
- Windows Server 2019
- A free M.2 key M or key B slot

Package content

- Converter
- User manual

Images











General

Form factor:	M.2 3042
Function:	bootable
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows Server 2019 Windows 11 Linux Kernel 5.15 or above
Slot:	PCIe

Interface

Connector 1:	1 x 59 pin M.2 key B+M male
Connector 2:	4 x SATA 6 Gb/s 7 pin plug

Technical characteristics

Data transfer rate:	6 Gb/s
RAID function:	JBOD 10 HyperDuo Virtual Disk 0 1

Physical characteristics

Length:	42 mm
Width:	30 mm
Height:	13 mm