

Delock Adapter USB Type-C™ male > DVI female (DP Alt Mode) 4K 30 Hz

Description

This adapter by Delock is suitable for the connection of a DVI monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface.



Item no. 61213

EAN: 4043619612130 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x DVI 24+5 female with nuts
- Chipset: Realtek RTD2171U
- DVI-D (Single Link), VGA not wired
- DisplayPort 1.4 specification
- · Resolution:

DVI up to 1920 x 1080 @ 60 Hz (depending on the system and the connected hardware) HDMI with the help of an adapter cable up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)

- Transfer of digital video signals
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- · USB bus powered
- Plug & Play
- Connectors: gold-plated
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm



· Colour: black

System requirements

- Chrome OS
- iPad Pro (2018)
- Linux Kernel 4.3 or above
- Mac OS 10.12 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- Windows 10 Mobile
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

• USB-CTM to DVI adapter

Images







General

| Function: | Plug & Play |
|-----------------------------|---|
| Specification: | DisplayPort 1.4 |
| Supported operating system: | Chrome OS Linux Kernel 4.3 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 10 Mobile Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) |

Interface

| Output: | 1 x DVI 24+5 female |
|---------|----------------------|
| Input: | 1 x USB Type-C™ male |

Technical characteristics

| Chipset: | Realtek RTD2171U |
|----------------------------|---|
| Maximum screen resolution: | 2560 x 1600 @ 60 Hz 3840 x 2160 @ 30 Hz 4096 x 2160 @ 24 Hz |
| Signal transmission: | video |

Physical characteristics

| Ferrite core: | 1 x |
|----------------------|-------------|
| Cable length: | 20 cm |
| Connector finishing: | gold-plated |
| Colour: | black |