TRAGANT®

Adapter USB 2.0 Type-A > 1 x Serial DB9 RS-232

Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port.

1,5 m

Item no. 62582

EAN: 4043619625826

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  1 x USB 2.0 Type-A male >
  1 x serial RS-232 DB9 male with nuts
- Chipset: Prolific PL2303RA
- Data transfer rate up to 128 Kbps
- Cable length: ca. 1.5 m

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

Images

Pin 1: Data Carrier Detect (DCD)
Pin 2: Received Data (RXD)
Pin 3: Transmit Data (TXD)
Pin 4: Data Transmit (DTR)
Pin 5: Ground (GND)

Pin 6: Data Set Ready (DSR)
Pin 7: Request To Send (RTS)
Pin 8: Clear To Send (CTS)
Pin 9: Ring Indicator (RI)

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

www.tragant.de
62582

2 / 3
03.02.2022

General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0

Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 male

Technical characteristics

Chipset:	Prolific PL2303RA
Data transfer rate:	up to 115,2 Kb/s
FIFO:	512 Byte
Data transmission:	asynchronous full duplex
UART:	USB to serial UART

Physical characteristics

Cable length incl. connector:	1.5 m
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double
Colour:	transparent black