Delock 2.5″ Converter SATA 22 pin > 2 x mSATA with RAID with Enclosure

Description

This converter by Delock enables the connection of up to two mSATA SSD and can be built in as 2.5″ disk. Therefor the converter will be installed into the system through the USB interface. When using more than one SSD, there is the possibility to use different RAID level.

Note

This product provides a chipset-based RAID function. Management and setting of the RAID mode is not possible via the operating system or BIOS. Different diagnostic software is not compatible with this solution.
The SMART function is not supported. JBOD is only supported on SATA controllers with port multiplier function.

Item no. 62594

EAN: 4043619625949

Country of origin: Taiwan, Republic of China

Package: Box

Specification

- Connectors:
  1 x SATA 6 Gb/s 22 pin plug
  2 x mSATA slot (full size)
- Chipset: Asmedia ASM1092R
- Form factor: 2.5″
- For 3.3 V mSATA module
- Also half size modules fit in
- Supports RAID 0, 1, JBOD
- RAID mode set by DIP switch on board
- 1 x LED for SATA host activity (green) and 2 x LED for mSATA SSD error (red)
- OS independent, no driver installation necessary

System requirements

- A free SATA 22 pin interface

Package content

• Converter
• 2.5″ enclosure
• Mounting material

Images

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

www.tragant.de
62594

2 / 2
09.05.2023