
Delock Converter SATA 22 pin > 1 x M.2 + 1 x mSATA

Description

This Delock converter enables the connection of a M.2 SSD in 2280, 2260, 2242 and 2230 format or an mSATA SSD in half size or full size format. If both slots are occupied, only the M.2 SSD can be used. The converter will be installed into the system internally through a SATA 22 pin interface.



Item no. 62670

EAN: 4043619626700

Country of origin: Taiwan, Republic of China

Package: Box

Specification

- Connector:
  1 x SATA 6 Gb/s 22 pin plug >
  1 x 67 pin M.2 key B slot
  1 x mSATA slot (full size)
- Interface: SATA
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.35 mm application of double-sided assembled modules supported
- LED indicator for power and activity
- PWM chipset: max. 3 A output current, short circuit protection, in-rush current suppression, thermal shutdown protection
- Bootable
- Dimensions (LxW): ca. 98 x 65.5 mm
- OS independent, no driver installation necessary

System requirements

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- A free SATA 22 pin interface

Package content

- Converter
- Mounting material
- User manual

Images





© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.