

## **Delock HDMI Audio Extractor 4K 30 Hz**

#### Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



Item no. 62692

EAN: 4043619626922 Country of origin: China Package: Retail Box

### **Specification**

• Connectors:

Input:

1 x HDMI-A 19 pin female

1 x 5 V DC jack 2.1 x 5.5 mm

Output:

1 x HDMI-A 19 pin female

1 x 3.5 mm 3 pin stereo jack female (audio)

1 x TOSLINK female S/PDIF

1 x RCA female S/PDIF

- Switchable between stereo and 5.1 channel
- High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8 bit), 1920 x 1080 @ 60 Hz (12 bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)





• Chipset: CS4344, 24 bit / 192 kHz

· Robust metal housing

• Power consumption: max. 2.5 W

• Dimensions (LxWxH): ca. 71 x 61 x 21 mm

### Power supply specification

· Wall power supply

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A

• Output: 5 V / 1 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

#### System requirements

• A free HDMI-A female

### **Package content**

- HDMI Audio Extractor
- · Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

### **Images**











#### General

Specification:

DTS Audio
High Speed HDMI
Dolby Digital
HDCP 1.4
LPCM

### Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x RCA female 1 x HDMI-A female 1 x TOSLINK female
Input:	1 x HDMI-A female 1 x 5 V DC female 5,5 mm x 2,1 mm

### **Technical characteristics**

Chipset:	Cirrus CS4344
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Video bandwidth:	300 MHz

# **Physical characteristics**

Housing colour:	black
Housing material:	metal
Length:	71 mm
Width:	61 mm
Height:	21 mm

## **Power supply**

Туре:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Output:	5 V / 1 A





Connector:	DC male 5.5 mm x 2.1 mm
Cable length:	1 m