

Delock Audio Converter Digital > Analogue with 3.5 mm Stereo Jack female

Description

The Delock audio converter converts the digital signal into an analogue stereo signal. At the input port of the device can be connected e. g. a digital DVD or Blu-Ray player and the digital signal will be applied either optically via TOSLINK or coaxial connection. At the output port the analogue signal will be transmitted through the RCA or Stereo jack connection to the analogue device.



Item no. 62722

EAN: 4043619627226

Country of origin: China

Package: White Box

Specification

- Connector:
 - Input:
 - 1 x TOSLINK female S/PDIF
 - 1 x Coaxial female S/PDIF
 - Output:
 - 2 x RCA female (red, white)
 - 1 x 3.5 mm 3 pin stereo jack female
 - 1 x DC 5 V power connector
- Supports different audio rates, e. g. 32, 44.1, 48 and 96 KHz
- Bit rate 24 Bit
- 1 x LED for power
- Current consumption: max. 250 mA
- Dimensions (LxWxH): ca. 63 x 41 x 21 mm

Power supply specification

- Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 2.1 mm
outside: ø ca. 5.5 mm
length: ca. 9 mm

System requirements

- Digital audio signal
- Connection cables

Package content

- Converter digital > analogue
- Power supply
- User manual

Images



General

LED indicator:	Power
----------------	-------

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 2 x RCA female (red, white)
Input:	1 x TOSLINK female S/PDIF 1 x Coaxial female S/PDIF

Technical characteristics

Bit rate:	24 Bit
Current consumption:	250 mA

Physical characteristics

Length:	63 mm
Width:	41 mm
Height:	21 mm