

# Delock Audio Converter Digital > Analogue with 3.5 mm Stereo Jack female with USB power supply

## Description

The Delock audio converter converts the digital signal into an analogue stereo signal. At the input port of the device can be connected e. g. a digital DVD or Blu-Ray player and the digital signal will be applied either optically via Toslink or coaxial connection. At the output port the analogue signal will be transmitted through the RCA or Stereo jack connection to the analogue device.



**Item no. 62723**

EAN: 4043619627233

Country of origin: China

Package: White Box

## Specification

- Connector:
  - Input:
    - 1 x Toslink female S/PDIF
    - 1 x Coaxial female S/PDIF
  - Output:
    - 2 x RCA female (red, white)
    - 1 x 3.5 mm 3 pin stereo jack female
    - 1 x USB Type Micro-B female (5 V power supply)
- Supports different audio rates, e. g. 32, 44.1, 48 and 96 KHz
- Bit rate 24 Bit
- 1 x LED for power
- Current consumption: max. 250 mA
- Dimensions (LxWxH): ca. 63 x 45 x 20 mm

## System requirements

- Digital audio signal

- Connection cables

---

## Package content

- Converter digital > analogue
- USB Type Micro-B to Type-A cable, length ca. 80 cm
- User manual

---

## Images



## General

LED indicator:	Power
----------------	-------

## Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 2 x RCA female (red, white)
Input:	1 x TOSLINK female S/PDIF 1 x Coaxial female S/PDIF

## Technical characteristics

Bit rate:	24 Bit
Current consumption:	250 mA

## Physical characteristics

Length:	63 mm
Width:	41 mm
Height:	21 mm