

Delock Audio Converter Analogue with 3.5 mm Stereo Jack female > Digital with USB power supply

Description

The Delock audio converter converts the analogue stereo signal into a digital signal. At the input port of the device can be connected two RCA cables to feed in the analogue source signal e. g. from a record player. At the output port the signal will be transmitted through a Toslink or coaxial connection.



Item no. 62724

EAN: 4043619627240

Country of origin: China

Package: White Box

Specification

- Connector:
 - Input:
 - 2 x RCA female (red, white)
 - 1 x 3.5 mm 3 pin stereo jack female
 - Output:
 - 1 x Toslink female S/PDIF
 - 1 x Coaxial female S/PDIF
 - 1 x USB Type Micro-B female (5 V power supply)
- Supports different audio rates, e. g. 32, 44.1, 48 and 96 KHz
- Bit rate 24 Bit
- 1 x LED for power
- Current consumption: max. 250 mA
- Dimensions (LxWxH): ca. 63 x 45 x 20 mm

System requirements


- Analogue audio signal

- Connection cables

Package content

- Converter analogue > digital
- USB Type Micro-B to Type-A cable, length ca. 80 cm
- User manual

Images



General

| | |
|----------------|-------|
| LED indicator: | Power |
|----------------|-------|

Interface

| | |
|---------|--|
| Output: | 1 x Coaxial female S/PDIF 1 x TOSLINK female S/PDIF |
| Input: | 2 x RCA female (red, white) 1 x 3.5 mm 3 pin stereo jack female |

Technical characteristics

| | |
|----------------------|--------|
| Bit rate: | 24 Bit |
| Current consumption: | 250 mA |

Physical characteristics

| | |
|---------|-------|
| Length: | 63 mm |
| Width: | 41 mm |
| Height: | 21 mm |