

Delock USB 3.1 Gen 1 Adapter USB Type-C™ male > 2 x USB 3.0 Type-A female + 1 x HDMI female (DP Alt Mode) 4K 30 Hz

Description

This adapter by Delock is suitable for the connection to a computer with USB-C™ interface and DisplayPort alternate mode support. It extends the system by two USB 3.0 Type-A interfaces as well as one HDMI interface. The adapter has a USB Type-C™ Power Delivery port. This allows the laptop to be charged while the adapter is in use, as well as providing additional power to the two USB Type-A connectors.



Item no. 62854

EAN: 4043619628544

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
 - 2 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x HDMI-A 19 pin female
 - 1 x USB Type-C™ Power Delivery female (optional for power supply)
- Chipset: Parade PS176 + VIA VL812
- DisplayPort 1.2, High Speed HDMI with Ethernet (HEC) and SuperSpeed USB specification
- HDMI specification:
 - Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
 - Transfer of audio and video signals
 - Supports 3D displays
 - Supports HDCP 1.4 and 2.2
- USB bus powered
- Plug & Play
- 1 x ferrite core

- Cable length without connectors: ca. 15 cm
- Colour: black

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.4.x, Mac OS 10.11
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to 2 x USB-A + HDMI Adapter

Images



General

Function:	Plug & Play
Specification:	SuperSpeed USB (USB 3.2 Gen 1) DisplayPort 1.2 High Speed HDMI with Ethernet HDCP 1.4 HDCP 2.2
Supported operating system:	Linux Kernel 4.x or above Mac OS 10.11 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Output:	1 x HDMI-A female 2 x USB 5 Gbps Type-A female
Input:	1 x USB 5 Gbps USB Type-C™ male

Technical characteristics

Chipset:	VIA VL812 Parade PS176
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio
Voltage:	USB bus powered 1 x USB Type-C™ Power Delivery female (optional for power supply)

Physical characteristics

Ferrite core:	1 x
Cable length:	15 cm



Connector finishing:	gold-plated
Colour:	black