

Navilock Connection Cable MD6 female serial > 2.5 mm 3 pin stereo jack male 90° TTL (5 V) 52 cm

Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to TTL 5 V signals. Compatible with TTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

Item no. 62886

EAN: 4043619628865

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x MD6 female >
 - 1 x 2.5 mm 3 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: unidirectional
- Cable gauge: 28 AWG
- Voltage: 5 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

System requirements

- A Navilock serial MD6 GNSS receiver

Package content

- Connection cable for GNSS receiver
- Navilock support CD

Images



General

| | |
|--------|------------|
| Style: | angled 90° |
|--------|------------|

Interface

| | |
|--------------|-----------------------------------|
| connector: | 1 x MD6 jack |
| Connector 1: | 1 x 2.5 mm 3 pin stereo jack male |

Technical characteristics

| | |
|----------|-----------------|
| Chipset: | ASIX ZT3221LEEY |
| Voltage: | 5 V |

Physical characteristics

| | |
|-------------------------------|-------|
| Cable colour: | black |
| Cable length incl. connector: | 52 cm |