


Navilock Connection Cable M8 female serial waterproof > 3.5 mm 3 pin stereo jack male 90° TTL (5 V) 1.2 m

Description

The waterproof connection cable by Navilock converts the serial signals universally for all M8 receivers to TTL 5 V signals. Compatible with TTL/CMOS 5.0 V this I/O interface is suitable for GPIO, UART, controller and CPU.





ca. 1,2 m

Item no. 62894

EAN: 4043619628940 Country of origin: Taiwan,

Republic of China

Package: Zip poly bag

Specification

- · Connectors:
 - 1 x M8 female >
 - 1 x 3.5 mm 3 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: unidirectional
- Cable gauge: 28 AWG
- Voltage: 5 VWaterproof
- Cable colour: black
- Length incl. connectors (L): ca. 1.2 m

System requirements

A Navilock serial M8 GNSS receiver





Package content

- Connection cable for GNSS receiver
- Navilock support CD

Images







General

Protection category:	waterproof
Style:	angled 90°

Interface

connector:	1 x M8 female
Connector 1:	1 x 3.5 mm 3 pin stereo jack male

Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	5 V

Physical characteristics

Cable colour:	black
Cable length incl. connector:	120 cm