

# Delock Cable voltage converter Floppy 4 pin male 5 V > SATA 15 pin receptacle 3.3 V + 5 V

### Description

Some devices, as e.g. 1.8" SATA SSDs, require an operating voltage of 3.3 V. This voltage converter by Delock is for the connection to a Floppy female port on a power supply and converts the voltage from 5 V to 3.3 V and 5 V.



30 cm

#### Item no. 62906

EAN: 4043619629060 Country of origin: China Package: Zip poly bag

## Specification

- Connectors: Input: 1 x Floppy 4 pin male > Output: 1 x SATA 15 pin receptacle
- Voltage: Floppy 4 pin male 5 V
  SATA 15 pin receptacle 3.3 V + 5 V
- Maximum output current: 2.0 A
- Cable gauge: 18 AWG
- Length without connectors: ca. 30 cm

### System requirements

• A free Floppy female port on the power supply





# Package content

• Cable voltage converter

### Images





### Interface

| Connector 1: | 1 x Floppy 4 pin male      |
|--------------|----------------------------|
| Connector 2: | 1 x SATA 15 pin receptacle |

### **Technical characteristics**

| Maximum current: | 2 A          |
|------------------|--------------|
| Voltage:         | 3.3 V<br>5 V |

## **Physical characteristics**

| Conductor gauge: | 18 AWG |
|------------------|--------|
| Length:          | 30 cm  |