

# **Navilock Connection Cable MD6 female serial > 3.5 mm 4 pin stereo jack male 90° LVTTL (3,3 V) 52 cm**

## **Description**

The connection cable by Navilock converts the serial signals for all MD6 receivers to LVTTL 3,3 V signals. Compatible with LVTTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

**Item no. 62926**

EAN: 4043619629268

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## **Specification**

- Connectors:
  - 1 x MD6 female >
  - 1 x 3.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEYY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 3.3 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

## **System requirements**

- A Navilock serial MD6 GNSS receiver

## **Package content**

- Connection cable for GNSS receiver
  - Navilock support CD
- 

## Images



## General

Style:	angled 90°
--------	------------

## Interface

connector:	1 x MD6 jack
Connector 1:	1 x 3.5 mm 4 pin audio stereo jack male

## Technical characteristics

Chipset:	ASIX ZT3221LECY
Voltage:	3.3 V

## Physical characteristics

Cable colour:	black
Cable length incl. connector:	52 cm