**DELOCK®**

we move the world

# Delock Adapter USB 2.0 Type-A male > 4 x Serial RS-232 DB9 male

## Description

The USB 2.0 to serial adapter by Delock enables you to connect 4 serial devices to a free USB port of your PC or laptop.

1,4 m

### Item no. 62947

EAN: 4043619629473

Country of origin: CHINA

Package: Retail Box

## Specification

- Connectors:
  1 x USB 2.0 Type-A male >
  4 x serial RS-232 DB9 male
- Chipset: FTDI FT4232H
- Data transfer rate up to 115.2 Kb/s
- Supports: UHCI / OHCI / EHCI
- Serial connector with screw
- Supports remote wake-up and power management
- Cable length: ca. 1.4 m

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.x, Mac ex OS 10.9
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 4 x Serial adapter
- Driver CD
- User manual

## Images

## General

| Function: | Plug & Play<br>Remote Wake-Up |
|---|---|
| Specification: | RS-232 (EIA / TIA)<br>USB 2.0 |
| Supported operating system: | Linux Kernel 2.6 or above<br>Mac OS 10.9 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8 32-bit<br>Windows 8 64-bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |
| LED indicator: | Power |

## Interface

| Connector 1: | 1 x USB 2.0 Type-A male |
|---|---|
| Connector 2: | 1 x Serial RS-232 DB9 plug |

## Technical characteristics

| Chipset: | FTDI FT4232H |
|---|---|
| Data transfer rate: | 4 x up to 115,2 Kbps |
| FIFO: | 4 x 2 KByte |
| Data transmission: | asynchronous<br>full duplex |
| Current consumption: | up to 130 mA |

## Physical characteristics

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

www.tragant.de
62947

3 / 4
18.10.2021

| | |
|---|---|
| Connector color: | red<br>yellow<br>green<br>violet |
| Housing material: | Plastic |
| Cable type: | USB AWM Style 2725 VW-1 |
| Cable colour: | black |
| Cable length incl. connector: | 1.4 m |
| Pin finishing: | gold-plated |
| Conductor gauge: | 28 AWG data line<br>24 AWG power line |
| Screw type: | #4-40 UNC |
| Shielding: | double |