

Delock Adapter USB Type-C[™] male > VGA female (DP Alt Mode) + USB Type-A + USB Type-C[™] PD

Description

This adapter by Delock is suitable for the connection of a VGA monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface. Additional the adapter has a USB 3.1 Type-A port and a USB-CTM port. The USB-CTM port can be used for power supply of the output device or to transfer data in USB 3.1 Gen 1 speed. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.



Item no. 62992

EAN: 4043619629923 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C[™] male >
 - 1 x VGA 15 pin female
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C[™] Power Delivery female (optional for power supply)
- Chipset: VIA VL101 + VL813 + ITE IT6516
- DisplayPort 1.1a specification
- Resolution up to WUXGA 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of analogue video signals
- USB bus powered
- Plug & Play
- · Gold-plated connectors
- 1 x ferrite core
- Metal housing
- Cable length without connectors: ca. 20 cm
- Colour: grey

DATASHEET



System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Mac ex OS 10.12.5
- PC or laptop with a free USB Type-C[™] port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt[™] 3 port

Package content

• USB-C[™] to VGA Adapter + USB Type-A

Images





General

| Function: | Plug & Play |
|-----------------------------|---|
| Supported operating system: | Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |

Interface

| Output: | 1 x VGA 15 pin female 1 x USB 5 Gbps Type-A female |
|---------|---|
| Input: | 1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male |

Technical characteristics

| Maximum screen resolution: |
|----------------------------|
|----------------------------|

Physical characteristics

| Cable length: |
|---------------|
|---------------|