

Delock Converter CVBS / YPbPr / VGA to HDMI with Scaler

Description

The Delock A/V converter converts an analogue video and audio signal to a digital HDMI signal. Thereby e.g. a VCR or game console can be connected to an HDMI monitor or Full HD TV. The inputs can be scaled via the integrated video processor to an HDMI output signal of 720p or 1080p with 50 or 60 Hz.



Item no. 63963

EAN: 4043619639632 Country of origin: China Package: Retail Box

Specification

Connectors:

Input:

1 x RCA female (CVBS)

3 x RCA female (YPbPr)

2 x RCA female (audio)

1 x VGA 15 pin female with nuts

1 x 3.5 mm 3 pin stereo jack female (audio)

1 x DC 5 V power connector

Output:

1 x HDMI-A 19 pin female

- Input switchable between CVBS / YPbPr / VGA
- Output switchable between 720p / 1080p, PAL / NTSC
- Resolution (CVBS input) PAL / NTSC
- Resolution (YPbPr input) 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Resolution (VGA input) up to 1920 x 1080 @ 60 Hz
- Resolution (HDMI output) 1280 x 720 or 1920 x 1080 @ 50 or 60 Hz
- Supports stereo audio
- Colour: black
- Dimensions (LxWxH): ca. 185 x 85 x 25 mm





Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements

- Monitor or TV with HDMI connector
- Connection cables

Package content

- Multi-AV to HDMI Converter
- Power supply
- User manual

Images











General

Specification: High Spe	ed HDMI
-------------------------	---------

Interface

Output:	1 x HDMI-A female
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 1 x 3.5 mm 3 pin stereo jack female 1 x RCA female (composite) 2 x RCA female (red, white) 1 x VGA 15 pin female 3 x RCA female (YPbPr)

Technical characteristics

Maximum screen resolution: 1920 x 1080 @ 60 Hz

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Length:	185 mm
Width:	85 mm
Height:	25 mm

Power supply

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Output:	5 V / 1 A
Connector:	DC male 5.5 mm x 2.1 mm