

Delock 3.5" USB 3.2 Gen 1 Front Panel 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB 3.2 Gen 1 Type-A and one USB 3.2 Gen 1 Type-C port. It will be connected to the motherboard internally via a pin header male port.



Integrated Card Reader

In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.

Item no. 64050

EAN: 4043619640508

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - external:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
 - 2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
 - 1 x SD slot
 - 1 x Micro SD slot
 - internal:
 - 1 x 19 pin USB 3.0 pin header female port on the cable
 - 1 x SATA 15 pin power connector
- Chipset: Genesys Logic GL3520, GL3224
- Data transfer rate up to:
 - SuperSpeed 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
 1. Slot Secure Digital
 - SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0

2. Slot Micro Secure Digital

MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro

- Cable data:
1 x 19 pin USB 3.0 pin header female cable, length ca. 54 cm (without connectors)
- 3.5" metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB 3.0 pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" front panel
- USB 3.0 pin header female cable
- Screws
- User manual

Images



General

| | |
|-----------------------------|--|
| Form factor: | 3.5" |
| Function: | Hot Swap Plug & Play |
| Supported operating system: | Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit |

Interface

| | |
|-----------|---|
| External: | 1 x Micro SD Slot 1 x SD slot 1 x USB 5 Gbps USB Type-C™ female 2 x USB 5 Gbps Type-A female |
| Internal: | 1 x 19 pin USB 5 Gbps pin header female 1 x SATA 15 pin power connector |

Technical characteristics

| | |
|---------------------|--|
| Chipset: | Genesys Logic GL3520 Genesys Logic GL3224 |
| Data transfer rate: | USB 5 Gbps up to 5 Gb/s |

Physical characteristics

| | |
|-------------------|--------|
| Housing material: | metal |
| Length: | 102 mm |
| Width: | 95 mm |
| Height: | 26 mm |
| Colour: | black |