

# Delock USB Type-A to SATA Converter with 3.5" Protection Cover

## Description

This converter by Delock can be connected via USB Type-A interface to a PC or laptop. Thus a **2.5" or 3.5"** SATA HDD or SSD with a 22 pin SATA interface can be used.

### Protection cover for 3.5" HDD

The included protection cover can be used to insert a HDD and to continue using the converter.



**Item no. 64086**

EAN: 4043619640867

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x USB 3.0 Type-A male
  - 1 x SATA 6 Gb/s 22 pin receptacle
- Chipset: JMicron JMS578
- For 2.5" and 3.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate:
  - USB 3.0 up to 5 Gb/s
  - SATA up to 6 Gb/s
- LED indicator
- Colour:
  - cable: black
  - protection cover: grey
- Cable length without connectors: ca. 45 cm
- Dimensions protection cover (LxWxH): ca. 184 x 109 x 32 mm

## Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 10 mm

---

## System requirements

- Chrome OS 75.0 or above
- Linux Kernel 3.4 or above
- Mac OS 10.14.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

---

## Package content

- Converter
- Protection cover
- Power supply
- User manual

---

## Images



## General

|                             |                                                                                                                                                                                    |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable for data medium:   | 3.5"<br>SSD or HDD                                                                                                                                                                 |
| Supported operating system: | Chrome OS 75.0 or above<br>Linux Kernel 3.4 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

|              |                                   |
|--------------|-----------------------------------|
| Connector 1: | 1 x USB 5 Gbps Type-A male        |
| Connector 2: | 1 x SATA 6 Gb/s 22 pin receptacle |
| connector 3: | 1 x DC jack                       |

## Technical characteristics

|                     |                                              |
|---------------------|----------------------------------------------|
| Chipset:            | JMicron JMS578                               |
| Data transfer rate: | USB 5 Gbps up to 5 Gb/s<br>SATA up to 6 Gb/s |

## Physical characteristics

|         |             |
|---------|-------------|
| Length: | 184 mm      |
| Width:  | 109 mm      |
| Height: | 32 mm       |
| Colour: | transparent |