

# Delock USB Type-C™ 3.2 Gen 2 to SATA Converter

## Description

This converter by Delock can be connected via USB Type-A interface to a PC or laptop. Thus a **2.5" or 3.5" SATA HDD or SSD** with a 22 pin SATA interface can be used.



**Item no. 64104**

EAN: 4043619641048

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 1 x SATA 6 Gb/s 22 pin receptacle
  - 1 x DC jack
- Chipset: VIA VL716
- For 2.5" and 3.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 6 Gb/s
- LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 72 x 29 x 14 mm

## Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.5 mm

outside: ø ca. 5.5 mm

length: ca. 10 mm

---

## System requirements

- Chrome OS 76.0 or above
- Linux Kernel 3.12 or above
- Mac OS 10.15.1 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

---

## Package content

- Converter
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Power supply
- User manual

---

## Images



## General

|                             |                                                                                                                                                                                                                |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable for data medium:   | 2.5"<br>3.5"                                                                                                                                                                                                   |
| Supported operating system: | Chrome OS 76.0 or above<br>Linux Kernel 3.12 or above<br>Mac OS 10.15.1 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

|              |                                    |
|--------------|------------------------------------|
| Connector 1: | 1 x USB 10 Gbps USB Type-C™ female |
| Connector 2: | 1 x SATA 6 Gb/s 22 pin receptacle  |
| connector 3: | 1 x DC jack                        |

## Technical characteristics

|                     |           |
|---------------------|-----------|
| Chipset:            | VIA VL716 |
| Data transfer rate: | 6 Gb/s    |

## Physical characteristics

|               |     |
|---------------|-----|
| Cable length: | 1 m |
|---------------|-----|