Delock USB Type-C™ Adapter to Gigabit LAN with Power Delivery port grey

Description

The adapter by Delock expands a PC or laptop by one network interface via the USB Type-C™ interface. In addition, the adapter can also be operated on a **Thunderbolt™ 3 interface**.

USB Power Delivery (USB PD 3.0) support up to 100 watt
The adapter has a **USB Type-C™ Power Delivery port** to connect the power supply of the laptop or tablet to charge it.

Small sturdy helper
Due to its small dimensions and its **sturdy housing,** this Delock adapter is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed.



Item no. 64116

EAN: 4043619641161

Country of origin: China

Package: Retail Box

Note

When using with MacBook, the driver has to be installed first.

Specification

- Connectors:
  1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male >
  1 x Gigabit LAN RJ45 jack
  1 x USB Type-C™ PD female (power supply)
- Chipset: ASIX AX88179
- SuperSpeed USB - 5 Gbps specification
- Data transfer rate:
  Ethernet up to 10 Mbps (Half/Full Duplex)
  Fast Ethernet up to 100 Mbps (Half/Full Duplex)
  Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
- Compatible with:
  IEEE 802.3: 10BASE-T
  IEEE 802.3u: 100BASE-TX
  IEEE 802.3ab: 1000BASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Supports Wake On LAN (WOL)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow control
- Supports 4k Jumbo Frames
- Output power for host: max. 100 W
- Housing material: aluminium / plastic
- LED indicator for power and activity
- USB bus powered
- Colour: grey
- Cable length incl. connectors: ca. 15.5 cm
- Dimensions (LxWxH): ca. 56 x 23.5 x 23.5 mm

System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Windows 8.1/8.1-64/10/10-64/11
- Laptop or tablet with a free USB Type-C™ or Thunderbolt™ 3 port

Package content

- USB Type-C™ Gigabit LAN adapter
- User manual

Images





© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Supported operating system:	Chrome OS Linux Kernel 5.4 or above Mac OS 10.15.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) Android 10.0 or above
LED indicator:	1 x

Interface

Connector 1:	1 x USB 5 Gbps USB Type-C™ male
Connector 2:	1 x Gigabit LAN RJ45 jack
connector 3:	1 x USB Type-C™ Power Delivery female

Technical characteristics

Chipset:	ASIX AX88179
Data transfer rate:	Gigabit Ethernet up to 100 Gbps Gigabit Ethernet up to 10 Gbps Gigabit Ethernet up to 1000 Mbps

Physical characteristics

Colour:	grey

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.