

Delock HDMI Extender Set over Cat.6 cable 4K 30 Hz

Description

This **HDMI** extender set by Delock can transmit high-resolution video / audio signals and an IR control signal over a singlenetwork cable. At **4K 30 Hz** resolution, distances of **up to 40 m** are possible, and at 1080p resolution, 70 m can be achieved. The set has wide applications in conference rooms, for tele-education or on large screens.



HDMI loop output

The transmitter has an HDMI loop output, so the signal can be **cascaded** to the next extender or to a monitor.

Power over Cable (PoC)

The set supports Power over Cable (PoC), so only the transmitter requires a power supply. The receiver is **powered via the network cable** and can therefore be used more flexible.

Screwable DC connection

The power supply with screwable connector ensures a secure and reliable connection - perfect **for professional installations** to avoid accidental disconnection.

Item no. 65832

EAN: 4043619658329 Country of origin: China Package: Retail Box

Specification

• Connectors Transmitter:

Input:

1 x HDMI-A female

1 x DC 12 V power connector screwable

Output:

1 x RJ45 jack

1 x HDMI-A female

1 x 3.5 mm 3 pin stereo jack female (IR)

• Connectors Receiver:

Input:

1 x RJ45 jack

1 x 3.5 mm 3 pin stereo jack female (IR)

DATASHEET



Output:

- 1 x HDMI-A female
- Transmission of audio and video signals
- Transmission of IR signals 30 60 kHz
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports EDID und HDCP
- Supports PoC (Power Over Cable)
- Power consumption: max. 3.0 W
- · Metal housing
- Wall-mount option
- · Colour: black
- Dimensions (LxWxH): ca. 80 x 69 x 17 mm

Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 12.0 V / 1.0 A / 12.0 W
- · Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements

- HDMI cable
- One Cat.5e or Cat.6 network cable

Package content

- HDMI transmitter
- HDMI receiver
- Infrared transmitter
- · Infrared receiver
- Power supply
- User manual



Images















General

|--|

Interface

Connector 1:	1 x HDMI-A female
Connector 2:	1 x RJ45 jack
connector 3:	1 x DC jack
connector 4:	1 x 3.5 mm 3 pin stereo jack female

Technical characteristics

3840 x 2160 @ 30 Hz Maximum screen resolution:

Physical characteristics

Housing colour:	black
Housing material:	metal