Delock Adapter SMC jack > BNC jack

Description

This adapter by Delock is suitable for connecting components of radio frequency technology.



Item no. 65857

EAN: 4043619658572

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
  1 x SMC jack >
  1 x BNC jack
- Housing material: Nickel plated brass
- Connector finishing: brass gold plated
- Impedance: 50 Ohm
- Frequency range: DC - 6 GHz
- VSWR: 1.45 / 1 GHz
- Operating temperature: -55 °C ~ 155 °C
- Length: ca. 22.5 mm
- Diameter: ca. 15 mm

System requirements

- Device with a free SMC port

Package content

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- RF Adapter

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Interface

Connector 1:	1 x SMC jack
Connector 2:	1 x BNC female

Technical characteristics

Frequency range:	DC - 6 GHz
Impedance:	50 Ω
Operating temperature:	-55 °C ~ 155 °C
VSWR:	1.45 / 1 GHz

Physical characteristics

Housing material:	brass gold plated
Diameter:	15 mm
Length:	22.5 mm

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.