

Delock Adapter SuperSpeed USB (USB 3.2 Gen 1) with USB Type-A male > Gigabit LAN 10/100/1000 Mbps compact white

Description

The adapter by Delock expands a PC or laptop by one network interface via the USB Type-A interface.



Item no. 65905

EAN: 4043619659050 Country of origin: China Package: Retail Box

Specification

- · Connectors:
 - 1 x USB 5 Gbps Type-A male
 - 1 x Gigabit LAN RJ45 jack
- Chipset: Realtek RTL8153
- SuperSpeed USB 5 Gbps specification
- Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

• Compatible with:

IEEE 802.3: 10BASE-T IEEE 802.3u: 100BASE-TX IEEE 802.3ab: 1000BASE-T

- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow



control

- Supports 9k Jumbo Frames
- Downwards compatible to USB 2.0
- · LED indicator for link and activity
- USB bus powered
- Colour: white
- Cable length incl. connectors: ca. 12.7 cm

System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.9 or above
- Windows 8.1/10/11
- PC or laptop with a free USB Type-A port

Package content

- USB Type-A Gigabit LAN adapter
- User manual

Images







General

Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	power and activity

Interface

Connector 1:	1 x USB 5 Gbps Type-A male
Connector 2:	1 x Gigabit LAN RJ45 jack

Technical characteristics

Chipset:	Realtek RTL8153
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1000 Mbps
Operating temperature:	0 °C ~ 55 °C

Physical characteristics

Cable length incl. connector:	12.7 cm
Colour:	white