

# Delock Adapter USB 2.0 Type-A to 1 x serial RS-232 DB9 3 m

## Description

This USB Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices etc.



**Item no. 65962**

EAN: 4043619659623

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x USB 2.0 Type-A male >
  - 1 x serial RS-232 DB9 male with screws
- Chipset: FTDI FT232
- Data transfer rate up to 921.6 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 3 m

## System requirements

- Linux Kernel 2.6 or above

- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port


---

## Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

---

## Images



## General

|                             |                                                                                                                                                                                 |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function:                   | Plug & Play                                                                                                                                                                     |
| Specification:              | USB 1.1<br>USB 2.0                                                                                                                                                              |
| Supported operating system: | Linux Kernel 2.6 or above<br>Mac OS 10.9 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

|              |                            |
|--------------|----------------------------|
| Connector 1: | 1 x USB 2.0 Type-A male    |
| Connector 2: | 1 x Serial RS-232 DB9 male |

## Technical characteristics

|                     |                                |
|---------------------|--------------------------------|
| Chipset:            | FTDI 232R                      |
| Data transfer rate: | up to 921.6 Kbps               |
| FIFO:               | 128 byte<br>256 Byte           |
| Data transmission:  | asynchronous<br>Bi-directional |
| UART:               | USB to serial UART             |

## Physical characteristics

|                |                            |
|----------------|----------------------------|
| Cable type:    | UL AWM 2725 80 °C 30V VW-1 |
| Cable colour:  | black                      |
| Cable length:  | 3 m (incl. connector)      |
| Pin finishing: | gold-plated                |

|            |              |
|------------|--------------|
| Shielding: | double       |
| Colour:    | grey / black |