

Delock DIP sliding switch 10-digit 2.54 mm pitch THT vertical black 2 pieces

Description


This DIP sliding switch by Delock is suitable for the solder mounting on a PCB.

THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



2 x

Item no. 66116

EAN: 4043619661169

Country of origin: China

Package: Tube


Specification

- Connectors:
2 x 10 soldering pin
- Number of positions: 10
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 MΩ / 500 VDC
- Withstanding voltage: 500 VAC / 1 minute
- Soldering temperature: 260 °C for ca. 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- Material: plastic
- Colour: black
- Dimensions (LxWxH): ca. 26.4 x 6.2 x 3.2 mm

Package content

- 2 x DIP sliding switch

Images



General

Mounting type:	Soldering
----------------	-----------

Interface

connector:	2 x 10 soldering pin
------------	----------------------

Technical characteristics

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

Physical characteristics

Pitch distance:	2.54 mm
Material:	Plastic
Length:	26.4 mm
Width:	6.2 mm
Height:	3.2 mm
Switch:	On / Off
Colour:	black