
Delock DIP flip switch piano 10-digit 2.54 mm pitch THT vertical blue 10 pieces

Description

This DIP flip switch by Delock is suitable for the through-hole mounting on a PCB.

THT Assembly Technology
The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

Multifunctional application
The DIP switch is mainly used in telecommunications, computers and measuring.



10 x

Item no. 66148

EAN: 4043619661480

Country of origin: China

Package: Tube

Specification

- Connectors:
  2 x 10 soldering pin
- Number of positions: 10
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 MΩ / 500 VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 - 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- Material: plastic
- Colour: blue
- Dimensions (LxWxH): ca. 26.9 x 10.8 x 9.4 mm

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.


Package content

- 10 x DIP flip switch

Images







© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Mounting type:	Soldering

Interface

connector:	2 x 10 soldering pin

Technical characteristics

Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC

Physical characteristics

Pitch distance:	2.54 mm
Material:	Plastic
Length:	26.9 mm
Width:	10.8 mm
Height:	9.4 mm
Switch:	On / Off
Colour:	blue

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.