

Delock VGA15 male to Terminal Block Adapter with Enclosure

Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.

Protection by enclosure

The plastic enclosure protects the PCB from dirt and damage.

Strain relief

The integrated strain relief fixes the cable in the enclosure.



Item no. 66258

EAN: 4043619662586

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x VGA 15 pin male with screws
 - 1 x 10 pin terminal block
- Pitch: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 51.8 x 34.4 x 21.0 mm

System requirements

- A free VGA interface

Package content

- Adapter
- 1 x strain relief
- 2 x locking screws

Images



Interface

| | |
|--------------|---------------------------|
| Connector 1: | 1 x VGA 15 pin male |
| Connector 2: | 1 x 10 pin terminal block |

Technical characteristics

| | |
|------------------------|-----------------|
| Operating temperature: | -20 °C ~ 105 °C |
|------------------------|-----------------|

Physical characteristics

| | |
|------------------|-------------|
| Pitch distance: | 3.81 mm |
| Conductor gauge: | 26 - 18 AWG |
| Length: | 51.8 mm |
| Width: | 34.4 mm |
| Height: | 21.0 mm |